

TO: Interested Parties / Applicant

FROM: John B. Chavez
Administrator
Office of Environmental Services

Notice of Decision - Approval

Please be advised that on behalf of the Commissioner of the Indiana Department of Environmental Management, I have issued a decision regarding the enclosed matter. Pursuant to IC 4-21.5-3-5 (f), this order will become effective within fifteen (15) calendar days from receipt of this notice unless a petition for review and a petition for stay of effectiveness is filed.

If you wish to challenge this decision, IC 4-21.5-3-7 requires that you file a petition for administrative review. This petition may include a request for stay of effectiveness and must be submitted to the Office Environmental Adjudication, 100 North Senate Avenue, Government Center North, Room 1049, Indianapolis, IN 46204, **within fifteen (15) calendar days from the receipt of this notice**. The filing of a petition for administrative review is complete on the earliest of the following dates that apply to the filing:

- (1) the date the document is delivered to the Office of Environmental Adjudication (OEA); or
- (2) the date of the postmark on the envelope containing the document, if the document is mailed to OEA by U.S. mail; or
- (3) The date on which the document is deposited with a private carrier, as shown by receipt issued by the carrier, if the document is sent to the OEA by private carrier.

The petition must include facts demonstrating that you are either the applicant, a person aggrieved or adversely affected by the decision or otherwise entitled to review by law. Please identify the permit, decision, or other order for which you seek review by permit number, name of the applicant, location, date of this notice and the following:

- (1) the name and address of the person making the request; and
- (2) the interest of the person making the request; and
- (3) identification of any persons represented by the person making the request; and
- (4) the reasons, with particularity, for the request; and
- (5) the issues, with particularity, proposed for considerations at any hearing; and
- (6) identification of the terms and conditions which, in the judgment of the person making the request, would be appropriate in the case in question to satisfy the requirements of the law governing documents of the type issued by the Commissioner.

If you have technical questions regarding the enclosed documents, please contact the Office of Environmental Services, Air Permits, at (317) 327-2234.

Enclosures

October 17, 2003

Mr. Werner Lorenz
Indiana Veneers Corporation
1211 East 24th Street
Indianapolis, IN 46205

RE: Minor Source Operating Permit
MSOP **097-17957-00031**

Dear Mr. Lorenz:

Enclosed is a Minor Source Operating Permit issued in approval of veneer production facility, located at 1211 East 24th Street, Indianapolis, Indiana 46205.

Please note that this approval has been issued with certain conditions. If the conditions are not acceptable, contact the Indianapolis Office of Environmental Services (OES) by letter or telephone within fifteen (15) days from the receipt of this letter. The OES will arrange a meeting to discuss the conditions in questions. If no agreement is reached, the Indianapolis Air Pollution Control Board may be petitioned within fifteen (15) days of the date of the meeting. The Board, after public notice and hearing, may sustain, modify, or rescind the conditions. Note that additional conditions may be included in this Minor Source Operating Permit.

Please keep this Permit (or a copy) on file at the facility (specified in the Permit) available for inspection by the OES and IDEM, Office of Air Quality (OAQ) personnel.

If you have any questions, please contact Ms. Monica Dick at (317) 327-2512. Thank you for your time and cooperation in this matter.

Sincerely,

Original Signed by John B. Chavez
John B. Chavez, Administrator

MBC

Attachments: MSOP 097-17957-00031x
Technical Support Document

cc: Mindy Hahn, IDEM, OAQ
files

**MINOR SOURCE OPERATING PERMIT
INDIANA DEPARTMENT OF ENVIRONMENTAL
MANAGEMENT
OFFICE OF AIR QUALITY
and the OFFICE OF ENVIRONMENTAL SERVICES**

**Indiana Veneers Corporation
1121 East 24th Street
Indianapolis, Indiana 46205**

(herein known as the Permittee) is hereby authorized to operate subject to the conditions contained herein, the emission units described in Section A (Source Summary) of this permit.

This permit is issued to the above mentioned company under the provisions of 326 IAC 2-1.1, 326 IAC 2-6.1, with conditions listed on the attached pages.

| | |
|--|--|
| Operation Permit No.: MSOP 097-17957-00031 | |
| Issued by: ORIGINAL SIGNED by JOHN B. CHAVEZ John B. Chavez Administrator, Office of Environmental Services | Issuance Date: October 17, 2003 Expiration Date: October 17, 2008 |

TABLE OF CONTENTS

A SOURCE SUMMARY

- A.1 General Information [326 IAC 2-5.1-3(c)] [326 IAC 2-6.1-4(a)]
- A.2 Emission Units and Pollution Control Equipment Summary
- A.3 Part 70 Permit Applicability [326 IAC 2-7-2]

B GENERAL CONDITIONS

- B.1 Permit No Defense [IC 13]
- B.2 Definitions
- B.3 Effective Date of the Permit [IC 13-15-5-3]
- B.4 Permit Term and Renewal [326 IAC 2-6.1-7(a)][326 IAC 2-1.1-9.5]
- B.5 Minor Source Operating Permit [326 IAC 2-6.1]
- B.6 Annual Notification [326 IAC 2-6.1-5(a)(5)]
- B.7 Preventive Maintenance Plan [326 IAC 1-6-3]
- B.8 Permit Revision [326 IAC 2-5.1-3(e)(3)][326 IAC 2-6.1-6]
- B.9 Inspection and Entry [326 IAC 2-5.1-3(e)(4)(B)][326 IAC 2-6.1-5(a)(4)][IC 13-14-2-2]
[IC 13-30-3-1]
- B.10 Transfer of Ownership or Operation [326 IAC 2-6.1-6(d)(3)]
- B.11 Annual Fee Payment [326 IAC 2-1.1-7]

C SOURCE OPERATION CONDITIONS

- C.1 Permit Revocation [326 IAC 2-1-9]
- C.2 Opacity [326 IAC 5-1]
- C.3 Fugitive Dust Emissions [326 IAC 6-4]
- C.4 Asbestos Abatement Projects [326 IAC 14-10][326 IAC 18][40 CFR 61, Subpart M]
- C.5 Performance Testing [326 IAC 3-6]
- C.6 Compliance Requirements [326 IAC 2-1.1-11]
- C.7 Compliance Monitoring [326 IAC 2-1.1-11]
- C.8 Monitoring Methods [326 IAC 3][40 CFR 60][40 CFR 63]
- C.9 Pressure Gauge and Other Instrument Specifications [326 IAC 2-1.1-11]
- C.10 Compliance Monitoring Plan - Preparation and Implementation
- C.11 Actions Related to Noncompliance Demonstrated by a Stack Test

Record Keeping and Reporting Requirements

- C.12 Malfunctions Report [326 IAC 1-6-2]
- C.13 Annual Emission Statement [326 IAC 2-6]
- C.14 General Record Keeping Requirements [326 IAC 2-6.1-2]
- C.15 General Reporting Requirements [326 IAC 2-1.1-11] [326 IAC 2-6.1-2] [IC 13-14-1-13]

D.1 FACILITY OPERATION CONDITIONS - 14.11 MMBtu/hr Wood-fired Boiler

Emission Limitations and Standards

- D.1.1 Particulate Matter Limitation (PM) [326 IAC 6-2-3][326 IAC 6-2-4]
- D.1.2 Preventive Maintenance Plan [326 IAC 1-6-3]

Compliance Determination Requirements

- D.1.3 Particulate Matter

Compliance Monitoring Requirements [326 IAC 2-5.1-3(e)(2)] [326 IAC 2-6.1-5(a)(2)]

- D.1.4 Cyclone Inspections
- D.1.5 Cyclone Failure Detection
- D.1.6 Visible Emissions Notations

Record Keeping and Reporting Requirements [326 IAC 2-5.1-3(e)(2)] [326 IAC 2-6.1-5(a)(2)]

D.1.7 Record Keeping Requirements

**Annual Notification
Malfunction Report**

SECTION A

SOURCE SUMMARY

This permit is based on information requested by the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ) and the City of Indianapolis, Office of Environmental Services (OES). The information describing the source contained in conditions A.1 through A.2 is descriptive information and does not constitute enforceable conditions. However, the Permittee should be aware that a physical change or a change in the method of operation that may render this descriptive information obsolete or inaccurate may trigger requirements for the Permittee to obtain additional permits or seek modification of this permit pursuant to 326 IAC 2, or change other applicable requirements presented in the permit application.

A.1 General Information [326 IAC 2-5.1-3(c)] [326 IAC 2-6.1-4(a)]

The Permittee owns and operates a stationary veneer production process with a wood waste combustion unit.

Authorized Individual: President
Source Address: 1211 East 24th Street, Indianapolis, IN 46205
Mailing Address: 1211 East 24th Street, Indianapolis, IN 46205
General Source Phone: (317) 926-2458
SIC Code: 2435
County Location: Marion
Source Location Status: Attainment for all criteria pollutants
Source Status: Minor Source Operating Permit
Minor Source, under PSD or Emission Offset Rules;
Minor Source, Section 112 of the Clean Air Act

A.2 Emissions Units and Pollution Control Equipment Summary

This stationary source is approved to operate the following emissions units and pollution control devices:

- (a) One (1) wood waste fired boiler, constructed in January of 1989, identified as 001, with a maximum heat input of 14.11 million British thermal units per hour (MM Btu/hr), 0.82 tons of wood waste per hour, using a Breslove Cyclone Separator as PM control.

SECTION B GENERAL CONDITIONS

THIS SECTION OF THE PERMIT IS BEING ISSUED UNDER THE PROVISIONS OF 326 IAC 2-1.1 AND 40 CFR 52.780, WITH CONDITIONS LISTED BELOW.

B.1 Permit No Defense [IC 13]

This permit to operate does not relieve the Permittee of the responsibility to comply with the provisions of the Indiana Environmental Management Law (IC 13-11 through 13-20; 13-22 through 13-25; and 13-30), the Air Pollution Control Law (IC 13-17) and the rules promulgated thereunder, as well as other applicable local, state, and federal requirements.

B.2 Definitions

Terms in this permit shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, the applicable definitions found in the statutes or regulations IC 13-11, 326 IAC 1-2, and 326 IAC 2-1.1-1 shall prevail.

B.3 Effective Date of the Permit [IC13-15-5-3]

Pursuant to IC 13-15-5-3, this permit becomes effective upon its issuance.

B.4 Permit Term and Renewal [326 IAC 2-6.1-7(a)][326 IAC 2-1.1-9.5]

This permit is issued for a fixed term of five (5) years from the issuance date of this permit, as determined in accordance with IC 4-21.5-3-5(f) and IC 13-15-5-3. Subsequent revisions of this permit do not affect the expiration date.

The Permittee shall apply for an operation permit renewal at least ninety (90) days prior to the expiration date. If a timely and sufficient permit application for a renewal has been made, this permit shall not expire and all terms and conditions shall continue in effect until the renewal permit has been issued or denied.

B.5 Modification to Permit [326 IAC 2]

All requirements and conditions of this operating permit shall remain in effect unless modified in a manner consistent with procedures established for modifications of construction permits pursuant to 326 IAC 2 (Permit Review Rules).

B.6 Annual Notification [326 IAC 2-6.1-5(a)(5)]

- (a) Annual notification shall be submitted to the Office of Air Quality stating whether or not the source is in operation and in compliance with the terms and conditions contained in this permit.
- (b) Noncompliance with any condition must be specifically identified. If there are any permit conditions or requirements for which the source is not in compliance at any time during the year, the Permittee must provide a narrative description of how the source did or will achieve compliance and the date compliance was, or will be, achieved. The notification must be signed by an authorized individual.
- (c) The annual notice shall cover the time period from January 1 to December 31 of the previous year, and shall be submitted in the format attached no later than March 1 of each year to:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Quality
100 North Senate Avenue, P.O. Box 6015
Indianapolis, IN 46206-6015

and

Office of Environmental Services
2700 South Belmont Avenue

Indianapolis, IN 46222

- (d) The notification shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, and the OES on or before the date it is due.

B.7 Preventive Maintenance Plan [326 IAC 1-6-3]

- (a) If required by specific condition(s) in Section D of this permit, the Permittee shall maintain and implement Preventive Maintenance Plans (PMPs) including the following information on each facility:
 - (1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;
 - (2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions; and
 - (3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.
- (b) The Permittee shall implement the PMPs, including any required record keeping, as necessary to ensure that failure to implement a PMP does not cause or contribute to an exceedance of any limitation on emissions or potential to emit.
- (c) A copy of the PMPs shall be submitted to IDEM, OAQ, and OES upon request and within a reasonable time, and shall be subject to review and approval by IDEM, OAQ, and OES. IDEM, OAQ, and OES may require the Permittee to revise its PMPs whenever lack of proper maintenance causes or is the primary contributor to an exceedance of any limitation on emissions or potential to emit. The PMP does not require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (d) To the extent the Permittee is required by 40 CFR Part 60/63 to have an Operation, Maintenance, and Monitoring (OMM) Plan for a unit, such Plan is deemed to satisfy the PMP requirements of 326 IAC 1-6-3 for that unit.

B.8 Permit Revision [326 IAC 2-5.1-3(e)(3)] [326 IAC 2-6.1-6]

- (a) Permit revisions are governed by the requirements of 326 IAC 2-6.1-6.
- (b) Any application requesting an amendment or modification of this permit shall be submitted to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

and

Office of Environmental Services
2700 South Belmont Avenue
Indianapolis, IN 46222

Any such application shall be certified by an "authorized individual" as defined by 326 IAC 2-1.1-1.

- (c) The Permittee shall notify the OAQ within thirty (30) calendar days of implementing a notice-only change. [326 IAC 2-6.1-6(d)]
- (d) No permit amendment or modification is required for the addition, operation or removal of a non-road engine, as defined in 40 CFR 89.2.

**B.9 Inspection and Entry [326 IAC 2-5.1-3(e)(4)(B)] [326 IAC 2-6.1-5(a)(4)][IC 13-14-2-2]
[IC 13-30-3-1]**

Upon presentation of proper identification cards, credentials, and other documents as may be required by law, and subject to the Permittee's right under all applicable laws and regulations to assert that the information collected by the agency is confidential and entitled to be treated as such, the Permittee shall allow IDEM, OAQ, the OES, U.S. EPA, or an authorized representative to perform the following:

- (a) Enter upon the Permittee's premises where a permitted source is located, or emissions related activity is conducted, or where records must be kept under the conditions of this permit;
- (b) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, have access to and copy, at reasonable times, any records that must be kept under this title or the conditions of this permit or any operating permit revisions;
- (c) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, inspect, at reasonable times, any processes, emissions units (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit or any operating permit revisions;
- (d) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with this permit or applicable requirements; and
- (e) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, utilize any photographic, recording, testing, monitoring, or other equipment for the purpose of assuring compliance with this permit or applicable requirements.

B.10 Transfer of Ownership or Operation [326 IAC 2-6.1-6(d)(3)]

Pursuant to [326 IAC 2-6.1-6(d)(3)] :

- (a) In the event that ownership of this source is changed, the Permittee shall notify IDEM, OAQ, Permits Branch and the OES within thirty (30) days of the change.
- (b) The written notification shall be sufficient to transfer the permit to the new owner by an notice-only change pursuant to 326 IAC 2-6.1-6(d)(3).
- (c) IDEM, OAQ, and the OES shall issue a revised permit.

The notification which shall be submitted by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1.

B.11 Annual Fee Payment [326 IAC 2-1.1-7]

- (a) The Permittee shall pay annual fees to IDEM, OAQ within thirty (30) calendar days of receipt of a billing.
- (b) The Permittee may call the following telephone numbers: 1-800-451-6027 or 317-233-4230 (ask for OAQ, I/M & Billing Section), to determine the appropriate permit fee.

SECTION C

SOURCE OPERATION CONDITIONS

| |
|---------------|
| Entire Source |
|---------------|

C.1 Permit Revocation [326 IAC 2-1.1-9]

Pursuant to 326 IAC 2-1.1-9 (Revocation of Permits), this permit operate may be revoked for any of the following causes:

- (a) Violation of any conditions of this permit.
- (b) Failure to disclose all the relevant facts, or misrepresentation in obtaining this permit.
- (c) Changes in regulatory requirements that mandate either a temporary or permanent reduction of discharge of contaminants. However, the amendment of appropriate sections of this permit shall not require revocation of this permit.
- (d) Noncompliance with orders issued pursuant to 326 IAC 1-5 (Episode Alert Levels) to reduce emissions during an air pollution episode.
- (e) For any cause which establishes in the judgment of IDEM and the OES, the fact that continuance of this permit is not consistent with purposes of this article.

C.2 Opacity [326 IAC 5-1]

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of thirty percent (30%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute non-overlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

C.3 Fugitive Dust Emissions [326 IAC 6-4]

The Permittee shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4 (Fugitive Dust Emissions).

C.4 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]

- (a) Notification requirements apply to each owner or operator. If the combined amount of regulated asbestos containing material (RACM) to be stripped, removed or disturbed is at least 260 linear feet on pipes or 160 square feet on other facility components, or at least thirty-five (35) cubic feet on all facility components, then the notification requirements of 326 IAC 14-10-3 are mandatory. All demolition projects require notification whether or not asbestos is present.
- (b) The Permittee shall ensure that a written notification is sent on a form provided by the Commissioner at least ten (10) working days before asbestos stripping or removal work or before demolition begins, per 326 IAC 14-10-3, and shall update such notice as necessary, including, but not limited to the following:
 - (1) When the amount of affected asbestos containing material increases or decreases by at least twenty percent (20%); or
 - (2) If there is a change in the following:

- (A) Asbestos removal or demolition start date;
 - (B) Removal or demolition contractor; or
 - (C) Waste disposal site.
- (c) The Permittee shall ensure that the notice is postmarked or delivered according to the guidelines set forth in 326 IAC 14-10-3(2).
- (d) The notice to be submitted shall include the information enumerated in 326 IAC 14-10-3(3).

All required notifications shall be submitted to:

Indiana Department of Environmental Management
Asbestos Section, Office of Air Quality
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

and

Office of Environmental Services
2700 South Belmont Avenue
Indianapolis, IN 46222

The notice shall include a signed certification from the owner or operator that the information provided in this notification is correct and that only Indiana licensed workers and project supervisors will be used to implement the asbestos removal project. The notifications do not require a certification by an "authorized individual" as defined by 326 IAC 2-7-1(34).

- (e) **Procedures for Asbestos Emission Control**
The Permittee shall comply with the applicable emission control procedures in 326 IAC 14-10-4 and 40 CFR 61.145(c). Per 326 IAC 14-10-1, emission control requirements are applicable for any removal or disturbance of RACM greater than three (3) linear feet on pipes or three (3) square feet on any other facility components or a total of at least 0.75 cubic feet on all facility components.
- (f) **Demolition and renovation**
The Permittee shall thoroughly inspect the affected facility or part of the facility where the demolition or renovation will occur for the presence of asbestos pursuant to 40 CFR 61.145(a).
- (g) **Indiana Accredited Asbestos Inspector**
The Permittee shall comply with 326 IAC 14-10-1(a) that requires the owner or operator, prior to a renovation/demolition, to use an Indiana Accredited Asbestos Inspector to thoroughly inspect the affected portion of the facility for the presence of asbestos. The requirement to use an Indiana Accredited Asbestos inspector is not federally enforceable.

Testing Requirements

C.5 Performance Testing [326 IAC 3-6]

- (a) Compliance testing on new emissions units shall be conducted within 60 days after

achieving maximum production rate, but no later than 180 days after initial start-up, if specified in Section D of this approval. All testing shall be performed according to the provisions of 326 IAC 3-6 (Source Sampling Procedures), except as provided elsewhere in this permit, utilizing any applicable procedures and analysis methods specified in 40 CFR 51, 40 CFR 60, 40 CFR 61, 40 CFR 63, 40 CFR 75, or other procedures approved by IDEM, OAQ.

A test protocol, except as provided elsewhere in this permit, shall be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

and

Office of Environmental Services
2700 South Belmont Avenue
Indianapolis, IN 46222

no later than thirty-five (35) days prior to the intended test date.

- (b) The Permittee shall notify IDEM, OAQ of the actual test date at least fourteen (14) days prior to the actual date.
- (c) Pursuant to 326 IAC 3-6-4(b), all test reports must be received by IDEM, OAQ and the OES not later than forty-five (45) days after the completion of the testing. An extension may be granted by the IDEM, OAQ and the OES, if the source submits to IDEM, OAQ, a reasonable written explanation not later than five (5) days prior to the end of the initial forty-five (45) day period.

Compliance Requirements [326 IAC 2-1.1-11]

C.6 Compliance Requirements [326 IAC 2-1.1-11]

The commissioner may require stack testing, monitoring, or reporting at any time to assure compliance with all applicable requirements by issuing an order under 326 IAC 2-1.1-11. Any monitoring or testing shall be performed in accordance with 326 IAC 3 or other methods approved by the commissioner or the U.S. EPA.

Compliance Monitoring Requirements

C.7 Compliance Monitoring [326 IAC 2-1.1-11]

Compliance with applicable requirements shall be documented as required by this permit. The Permittee shall be responsible for installing any necessary equipment and initiating any required monitoring related to that equipment. All monitoring and record keeping requirements not already legally required shall be implemented when operation begins.

C.8 Monitoring Methods [326 IAC 3][40 CFR 60][40 CFR 63]

Any monitoring or testing required by Section D of this permit shall be performed according to the provisions of 326 IAC 3, 40 CFR 60, Appendix A, 40 CFR 60, Appendix B, 40 CFR 63, or other approved methods as specified in this permit.

C.9 Pressure Gauge and Other Instrument Specifications [326 IAC 2-1.1-11] [326 IAC 2-7-5(3)]
[326 IAC 2-7-6(1)]

- (a) Whenever a condition in this permit requires the measurement of total static pressure drop across any part of the unit or its control device, the gauge employed shall have a scale such that the expected normal reading shall be no less than twenty percent (20%) of full scale and be accurate within plus or minus two percent ($\pm 2\%$) of full scale reading.
- (b) Whenever a condition in this permit requires the measurement of a (*temperature or flow rate*), the instrument employed shall have a scale such that the expected normal reading shall be no less than twenty percent (20%) of full scale and be accurate within plus or minus two percent ($\pm 2\%$) of full scale reading.
- (c) The Preventive Maintenance Plan for the pH meter shall include calibration using known standards. The frequency of calibration shall be adjusted such that the typical error found at calibration is less than one pH point.
- (c) The Permittee may request the IDEM, OAQ approve the use of a pressure gauge or other instrument that does not meet the above specifications provided the Permittee can demonstrate an alternative pressure gauge or other instrument specification will adequately ensure compliance with permit conditions requiring the measurement of pressure drop or other parameters.

C.10 Compliance Response Plan - Preparation and Implementation

- (a) The Permittee is required to prepare a Compliance Response Plan (CRP) for each compliance monitoring condition of this permit. If a Permittee is required to have an Operation, Maintenance and Monitoring (OMM) Plan under 40 CFR 60/63, such plans shall be deemed to satisfy the requirements for a CRP for those compliance monitoring conditions. A CRP shall be submitted to IDEM, OAQ and the OES upon request. The CRP shall be prepared within ninety (90) days after issuance of this permit by the Permittee, supplemented from time to time by the Permittee, maintained on site, and comprised of:
 - (1) Reasonable response steps that may be implemented in the event that a response step is needed pursuant to the requirements of Section D of this permit; and an expected time frame for taking reasonable response steps.
 - (2) If, at any time, the Permittee takes reasonable response steps that are not set forth in the Permittee's current Compliance Response Plan or Operation, Maintenance and Monitoring (OMM) Plan, the Permittee shall amend its Compliance Response Plan or Operation, Maintenance and Monitoring (OMM) Plan to include such response steps taken.

The OMM Plan shall be submitted within the time frames specified by the applicable 40 CFR60/63 requirement.

- (b) For each compliance monitoring condition of this permit, reasonable response steps shall be taken when indicated by the provisions of that compliance monitoring condition as follows:
 - (1) Reasonable response steps shall be taken as set forth in the Permittee's current Compliance Response Plan or Operation, Maintenance and Monitoring (OMM) Plan; or
 - (2) If none of the reasonable response steps listed in the Compliance Response Plan or Operation, Maintenance and Monitoring (OMM) Plan is applicable or

responsive to the excursion, the Permittee shall devise and implement additional response steps as expeditiously as practical. Taking such additional response steps shall not be considered a deviation from this permit so long as the Permittee documents such response steps in accordance with this condition.

- (3) If the Permittee determines that additional response steps would necessitate that the emissions unit or control device be shut down, the IDEM, OAQ shall be promptly notified of the expected date of the shut down, the status of the applicable compliance monitoring parameter with respect to normal, and the results of the actions taken up to the time of notification.
- (4) Failure to take reasonable response steps shall be considered a deviation of the permit.
- (c) The Permittee is not required to take any further response steps for any of the following reasons:
 - (1) A false reading occurs due to the malfunction of the monitoring equipment and prompt action was taken to correct the monitoring equipment.
 - (2) The Permittee has determined that the compliance monitoring parameters established in the permit conditions are technically inappropriate, has previously submitted a request for a minor permit modification to the permit, and such request has not been denied.
 - (3) An automatic measurement was taken when the process was not operating.
 - (4) The process has already returned or is returning to operating within "normal" parameters and no response steps are required.
- (d) Except as otherwise provided by a rule or provided specifically in Section D, all monitoring as required in Section D shall be performed when the emission unit is operating, except for time necessary to perform quality assurance and maintenance activities.

C.11 Actions Related to Noncompliance Demonstrated by a Stack Test

- (a) When the results of a stack test performed in conformance with Section C - Performance Testing, of this permit exceed the level specified in any condition of this permit, the Permittee shall take appropriate response actions. The Permittee shall submit a description of these response actions to IDEM, OAQ, within thirty (30) days of receipt of the test results. The Permittee shall take appropriate action to minimize excess emissions from the affected emissions unit while the response actions are being implemented.
- (b) A retest to demonstrate compliance shall be performed within one hundred twenty (120) days of receipt of the original test results. Should the Permittee demonstrate to IDEM, OAQ that retesting in one-hundred and twenty (120) days is not practicable, IDEM, OAQ may extend the retesting deadline.
- (c) IDEM, OAQ reserves the authority to take any actions allowed under law in response to noncompliant stack tests.

The response action documents submitted pursuant to this condition do not require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1.

Record Keeping and Reporting Requirements

C.12 Malfunctions Report [326 IAC 1-6-2]

Pursuant to 326 IAC 1-6-2 (Records; Notice of Malfunction):

- (a) A record of all malfunctions, including startups or shutdowns of any facility or emission control equipment, which result in violations of applicable air pollution control regulations or applicable emission limitations shall be kept and retained for a period of three (3) years and shall be made available to the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ) or appointed representative upon request.
- (b) When a malfunction of any facility or emission control equipment occurs which lasts more than one (1) hour, said condition shall be reported to OAQ, using the Malfunction Report Forms (2 pages). Notification shall be made by telephone or facsimile, as soon as practicable, but in no event later than four (4) daytime business hours after the beginning of said occurrence.
- (c) Failure to report a malfunction of any emission control equipment shall constitute a violation of 326 IAC 1-6, and any other applicable rules. Information of the scope and expected duration of the malfunction shall be provided, including the items specified in 326 IAC 1-6-2(a)(1) through (6).
- (d) Malfunction is defined as any sudden, unavoidable failure of any air pollution control equipment, process, or combustion or process equipment to operate in a normal and usual manner. [326 IAC 1-2-39]

C.13 Emission Statement [326 IAC 2-6]

- (a) The Permittee shall submit an annual emission statement certified pursuant to the requirements of 326 IAC 2-6, that must be received by April 15 of each year and must comply with the minimum requirements specified in 326 IAC 2-6-4. The annual emission statement shall meet the following requirements:
 - (1) Indicate estimated actual emissions of criteria pollutants from the source, in compliance with 326 IAC 2-6 (Emission Reporting);
 - (2) Indicate estimated actual emissions of regulated pollutants (as defined by 326 IAC 2-7-1(32) "Regulated pollutant which is used only for purposes of Section 19 of this rule") from the source, for purposes of Part 70 fee assessment.
- (b) The annual emission statement covers the twelve (12) consecutive month time period starting December 1 and ending November 30. The annual emission statement must be submitted to:

Indiana Department of Environmental Management
Technical Support and Modeling Section, Office of Air Quality
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

and

Office of Environmental Services
2700 South Belmont Avenue
Indianapolis, IN 46222

- (c) The annual emission statement required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ and the OES on or before the date it is due.

The submittal by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1.

C.14 General Record Keeping Requirements [326 IAC 2-6.1-5]

- (a) Records of all required monitoring data, reports and support information required by this permit shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be physically present or electronically accessible at the source location for a minimum of three (3) years. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner or the OES makes a request for records to the Permittee, the Permittee shall furnish the records to the Commissioner or the OES within a reasonable time.
- (b) Unless otherwise specified in this permit, all record keeping requirements not already legally required shall be implemented when operation begins.

C.15 General Reporting Requirements [326 IAC 2-1.1-11] [326 IAC 2-6.1-2] [IC 13-14-1-13]

- (a) Reports required by conditions in Section D of this permit shall be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

and

Office of Environmental Services
2700 South Belmont Avenue
Indianapolis, IN 46222

- (b) Unless otherwise specified in this permit, any notice, report, or other submission required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, and the OES on or before the date it is due.
- (c) Unless otherwise specified in this permit, any quarterly report required in Section D of this permit shall be submitted within thirty (30) days of the end of the reporting period. The report does not require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (d) The first report shall cover the period commencing on the date of issuance of this permit and ending on the last day of the reporting period. Reporting periods are based on calendar years.

SECTION D.1

FACILITY OPERATION CONDITIONS

Facility Description:

One (1) wood waste fired boiler, constructed in January of 1989, identified as 001, with a maximum heat input of 14.11 million British thermal units per hour (MM Btu/hr), 0.82 tons of wood waste per hour, using a Breslove Cyclone Separator as PM control.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards

D.1.1 Particulate Emission Limitations [326 IAC 6-1-2] [326 IAC 6-2-4]

Pursuant to 326 IAC 6-1-2 (Particulate Emission Limitations) the PM emissions from the 14.11 MMBtu per hour heat input boiler shall be limited to 0.6 pounds per MMBtu heat input. Compliance with this limit supersedes the requirements of 326 IAC 6-2-4.

D.1.2 Preventive Maintenance Plan [326 IAC 1-6-3]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for this facility and its control device.

Compliance Determination Requirements

D.1.3 Particulate Matter

In order to demonstrate compliance with D.1.1, the cyclone shall operate at all times the boiler is combusting wood.

Compliance Monitoring Requirements [326 IAC 2-5.1-3(e)(2)] [326 IAC 2-6.1-5(a)(2)]

D.1.4 Cyclone Inspections

An inspection shall be performed each calendar quarter of the cyclone controlling the boiler 001. A cyclone inspection shall be performed within three months of redirecting vents to the atmosphere and every three months thereafter. Inspections are optional when venting to the indoors. Inspections required by this condition shall not be performed in consecutive months.

D.1.5 Cyclone Failure Detection

In the event that cyclone failure has been observed:

Failed units and the associated process will be shut down immediately until the failed units have been repaired or replaced. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions). Failure to take response steps in accordance with Section C - Compliance Response Plan - Preparation, Implementation, Records, and Reports, shall be considered a violation of this permit.

D.1.6 Visible Emissions Notations

- (a) Visible emission notations of the boiler 001 stack exhaust shall be performed once per shift during normal daylight operations when exhausting to the atmosphere. A trained employee shall record whether emissions are normal or abnormal.
- (b) For processes operated continuously, "normal" means those conditions prevailing, or expected to prevail, eighty percent (80%) of the time the process is in operation, not counting startup or shut down time.
- (c) In the case of batch or discontinuous operations, readings shall be taken during that part

of the operation that would normally be expected to cause the greatest emissions.

- (d) A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the appearance and characteristics of normal visible emissions for that specific process.
- (e) The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when an abnormal emission is observed. Failure to take response steps in accordance with Section C - Compliance Response Plan - Preparation and Implementation shall be considered a violation of this permit.

Record Keeping and Reporting Requirements [326 IAC 2-5.1-3(e)(2)] [326 IAC 2-6.1-5(a)(2)]

D.1.7 Record Keeping Requirements

- (a) To document compliance with Condition D.1.6, the Permittee shall maintain records of visible emission notations of the boiler 001 stack exhaust once per shift.
- (b) To document compliance with Conditions D.1.2 and D.1.4, the Permittee shall maintain records of any additional inspections prescribed by the Preventive Maintenance Plan.
- (c) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
COMPLIANCE BRANCH
and OFFICE OF ENVIRONMENTAL SERVICES**

**MINOR SOURCE OPERATING PERMIT
ANNUAL NOTIFICATION**

This form should be used to comply with the notification requirements under 326 IAC 2-6.1-5(a)(5).

| | |
|----------------------|---|
| Company Name: | Indiana Veneers Corporation |
| Address: | 1121 East 24th Street |
| City: | Indianapolis, IN 46205 |
| Phone #: | (317) 926-2458 |
| MSOP #: | 097-17957-00031 |

I hereby certify that **Indiana Veneers Corporation** is

☒ still in operation.

☐ no longer in operation.

I hereby certify that **Indiana Veneers Corporation** is

☒ in compliance with the requirements of MSOP 097-17957-00031.

☐ not in compliance with the requirements of MSOP 097-17957-00031.

| |
|---------------------------------------|
| Authorized Individual (typed): |
| Title: |
| Signature: |
| Date: |

If there are any conditions or requirements for which the source is not in compliance, provide a narrative description of how the source did or will achieve compliance and the date compliance was, or will be achieved.

| |
|-----------------------|
| Noncompliance: |
| |
| |
| |
| |

MALFUNCTION REPORT

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
FAX NUMBER - 317 233-5967**

**This form should only be used to report malfunctions applicable to Rule 326 IAC 1-6
and to qualify for the exemption under 326 IAC 1-6-4.**

THIS FACILITY MEETS THE APPLICABILITY REQUIREMENTS BECAUSE IT HAS POTENTIAL TO EMIT 25 TONS/YEAR PARTICULATE MATTER ?____, 25 TONS/YEAR SULFUR DIOXIDE ?____, 25 TONS/YEAR NITROGEN OXIDES?____, 25 TONS/YEAR VOC ?____, 25 TONS/YEAR HYDROGEN SULFIDE ?____, 25 TONS/YEAR TOTAL REDUCED SULFUR ?____, 25 TONS/YEAR REDUCED SULFUR COMPOUNDS ?____, 25 TONS/YEAR FLUORIDES ?____, 100TONS/YEAR CARBON MONOXIDE ?____, 10 TONS/YEAR ANY SINGLE HAZARDOUS AIR POLLUTANT ?____, 25 TONS/YEAR ANY COMBINATION HAZARDOUS AIR POLLUTANT ?____, 1 TON/YEAR LEAD OR LEAD COMPOUNDS MEASURED AS ELEMENTAL LEAD ?____, OR IS A SOURCE LISTED UNDER 326 IAC 2-5.1-3(2) ?____. EMISSIONS FROM MALFUNCTIONING CONTROL EQUIPMENT OR PROCESS EQUIPMENT CAUSED EMISSIONS IN EXCESS OF APPLICABLE LIMITATION _____.

THIS MALFUNCTION RESULTED IN A VIOLATION OF: 326 IAC _____ OR, PERMIT CONDITION # _____ AND/OR PERMIT LIMIT OF _____

THIS INCIDENT MEETS THE DEFINITION OF 'MALFUNCTION' AS LISTED ON REVERSE SIDE ? Y N

THIS MALFUNCTION IS OR WILL BE LONGER THAN THE ONE (1) HOUR REPORTING REQUIREMENT ? Y N

COMPANY: _____ PHONE NO. () _____
LOCATION: (CITY AND COUNTY) _____
PERMIT NO. _____ AFS PLANT ID: _____ AFS POINT ID: _____ INSP: _____
CONTROL/PROCESS DEVICE WHICH MALFUNCTIONED AND REASON: _____

DATE/TIME MALFUNCTION STARTED: ____/____/19____ AM / PM

ESTIMATED HOURS OF OPERATION WITH MALFUNCTION CONDITION: _____

DATE/TIME CONTROL EQUIPMENT BACK-IN SERVICE ____/____/19____ AM/PM

TYPE OF POLLUTANTS EMITTED: TSP, PM-10, SO2, VOC, OTHER: _____

ESTIMATED AMOUNT OF POLLUTANT EMITTED DURING MALFUNCTION: _____

MEASURES TAKEN TO MINIMIZE EMISSIONS: _____

REASONS WHY FACILITY CANNOT BE SHUTDOWN DURING REPAIRS:

CONTINUED OPERATION REQUIRED TO PROVIDE ESSENTIAL* SERVICES: _____
CONTINUED OPERATION NECESSARY TO PREVENT INJURY TO PERSONS: _____
CONTINUED OPERATION NECESSARY TO PREVENT SEVERE DAMAGE TO EQUIPMENT: _____
INTERIM CONTROL MEASURES: (IF APPLICABLE) _____

MALFUNCTION REPORTED BY: _____ TITLE: _____
(SIGNATURE IF FAXED)

MALFUNCTION RECORDED BY: _____ DATE: _____ TIME: _____

*SEE PAGE 2

Please note - This form should only be used to report malfunctions applicable to Rule 326 IAC 1-6 and to qualify for the exemption under 326 IAC 1-6-4.

326 IAC 1-6-1 Applicability of rule

Sec. 1. This rule applies to the owner or operator of any facility required to obtain a permit under 326 IAC 2-5.1 or 326 IAC 2-6.1.

326 IAC 1-2-39 "Malfunction" definition

Sec. 39. Any sudden, unavoidable failure of any air pollution control equipment, process, or combustion or process equipment to operate in a normal and usual manner.

***Essential services** are interpreted to mean those operations, such as, the providing of electricity by power plants. Continued operation solely for the economic benefit of the owner or operator shall not be sufficient reason why a facility cannot be shutdown during a control equipment shutdown.

If this item is checked on the front, please explain rationale:

**Indiana Department of Environmental Management
Office of Air Quality**

and

Indianapolis Office of Environmental Services

**Technical Support Document (TSD) for a Minor Source Operation Permit
(MSOP)**

Source Background and Description

| | |
|------------------|---|
| Source Name: | Indiana Veneers Corporation |
| Source Location: | 1121 East 24 th Street, Indianapolis, IN 46205 |
| County: | Marion |
| Permit No.: | MSOP097-17957-00031 |
| SIC Code: | 2435 |
| Permit Reviewer: | Holly M. Stockrahm |

The Office of Air Quality (OAQ) and Office of Environmental Service (OES) have reviewed an application from Indiana Veneers Corporation relating to the operation of a veneer production operation with a wood waste combustion boiler. There are no woodworking operations or other emission units at the source. The source received logs (barkless) from a supplier, the wood is wetted and then the source slices veneer off of the logs. The logs must be wetted in order to for the veneer to remain intact so the water is integral to the process and the potential to emit of particulate matter is negligible. The scraps from the process are burned in the only emission unit, a wood waste fired boiler.

Unpermitted Emission Units and Pollution Control Equipment

- (a) One (1) wood waste fired boiler, constructed in January of 1989, identified as 001, with a maximum heat input of 14.11 million British thermal units per hour (MM Btu/hr), 0.82 tons of wood waste per hour, using a Breslove Cyclone Separator as particulate control.

New Emission Units and Pollution Control Equipment

There are no new construction activities included in this permit.

Existing Approvals

The source has received a small source certification, issued on July 30, 1998, for wooden veneer production and wood waste combustion.

Enforcement Issue

There are no enforcement actions pending at this time.

Recommendation

The staff recommends to the Commissioner that the operation be approved. This recommendation is based on the following facts and conditions:

Unless otherwise stated, information used in this review was derived from the application and additional information submitted by the applicant.

An application for the purposes of this review was received on July 17, 2003.

Emission Calculations

See Appendix A of this document for detailed emissions calculations (Appendix A, 2 pages).

Potential To Emit of Source Before Controls

Pursuant to 326 IAC 2-1.1-1(16), Potential to Emit is defined as “the maximum capacity of a stationary source or emissions unit to emit any air pollutant under its physical and operational design. Any physical or operational limitation on the capacity of a source to emit an air pollutant, including air pollution control equipment and restrictions on hours of operation or type or amount of material combusted, stored, or processed shall be treated as part of its design if the limitation is enforceable by the U. S. EPA, the department, or the appropriate local air pollution control agency.”

This table reflects the PTE before controls for the emission units. Control equipment is not considered federally enforceable until it has been required in a federally enforceable permit.

| Pollutant | Potential To Emit (tons/year) |
|-----------------|-------------------------------|
| PM | 20 |
| PM-10 | 20 |
| SO ₂ | 1.5 |
| VOC | 0.8 |
| CO | 5.6 |
| NO _x | 30 |

| HAP's | Potential To Emit (tons/year) |
|-------------------|-------------------------------|
| acrolein | 0.25 |
| benzene | 0.26 |
| formaldehyde | 0.27 |
| hydrogen chloride | 1.2 |
| styrene | 0.12 |
| Total | 2.1 |

- (a) The potential to emit (as defined in 326 IAC 2-1.1-1(16)) of all criteria pollutants is less than 100 tons per year. Therefore, the source is not subject to the provisions of 326 IAC 2-7.
- (b) The potential to emit (as defined in 326 IAC 2-1.1-1(16)) of any single HAP is less than ten (10) tons per year and the potential to emit (as defined in 326 IAC 2-1.1-1(16)) of a combination of HAPs is less than twenty-five (25) tons per year. Therefore, the source is not subject to the provisions of 326 IAC 2-7.
- (c) The potential to emit (as defined in 326 IAC 2-1.1-1(16)) of NO_x is equal to or greater than 25 tons per year, but less than 100 tons per year. Therefore, the source is subject to the provisions of 326 IAC 2-6.1.

(d) Fugitive Emissions

Since this type of operation is not one of the twenty-eight (28) listed source categories under 326 IAC 2-2 and since there are no applicable New Source Performance Standards that were in effect on August 7, 1980, the fugitive particulate matter (PM) and volatile organic compound (VOC) emissions are not counted toward determination of PSD and Emission Offset applicability.

County Attainment Status

The source is located in Marion County.

| Pollutant | Status |
|-----------------|------------------------|
| PM-10 | Attainment |
| SO ₂ | Maintenance Attainment |
| NO ₂ | Attainment |
| Ozone | Maintenance Attainment |
| CO | Maintenance Attainment |
| Lead | Maintenance Attainment |

- (a) Volatile organic compounds (VOC) are precursors for the formation of ozone. Therefore, VOC emissions are considered when evaluating the rule applicability relating to the ozone standards. Marion County has been designated as attainment or unclassifiable for ozone. Therefore, VOC emissions were reviewed pursuant to the requirements for Prevention of Significant Deterioration (PSD), 326 IAC 2-2.
- (b) Marion County has been classified as attainment or unclassifiable for all other criteria pollutants. Therefore, these emissions were reviewed pursuant to the requirements for Prevention of Significant Deterioration (PSD), 326 IAC 2-2.
- (c) Fugitive Emissions
Since this type of operation is not one of the 28 listed source categories under 326 IAC 2-2 and 326 IAC 2-3, the fugitive particulate matter (PM) and volatile organic compound (VOC) emissions are not counted toward determination of PSD and Emission Offset applicability.

Source Status

Existing Source PSD Definition (emissions after controls, based on 8,760 hours of operation per year at rated capacity and/ or as otherwise limited):

| Pollutant | Emissions (ton/yr) |
|-----------------|-----------------------|
| PM | 20 |
| PM10 | 20 |
| SO ₂ | 1.5 |
| VOC | 0.8 |
| CO | 5.6 |
| NO _x | 30 |

This existing source is not a major stationary source because no attainment regulated pollutant is emitted at a rate of 250 tons per year or more and it is not in one of the 28 listed source categories.

Part 70 Permit Determination

This existing source is not subject to the Part 70 Permit requirements because the potential to emit (PTE) of:

- (a) each criteria pollutant is less than 100 tons per year,
- (b) a single hazardous air pollutant (HAP) is less than 10 tons per year, and
- (c) any combination of HAPs is less than 25 tons/year.

Federal Rule Applicability

- (a) The New Source Performance Standards (NSPS)(326 IAC 12 and 40 CFR Part 60, Subpart Dc) is not applicable to the boiler, 001, because it was constructed on January 22, 1989, which is before the applicability date of June 9, 1989 even though it has a maximum design heat input capacity between 10 and 100 MM Btu/hr.
- (b) There are no National Emission Standards for Hazardous Air Pollutants (NESHAPs) (326 IAC 14 and 40 CFR Part 63) applicable to this boiler.

State Rule Applicability - Entire Source

326 IAC 2-2 (Prevention of Significant Deterioration (PSD))

The source was constructed in 1989. The source is not in 1 of 28 source categories defined in 326 IAC 2-2-1(p)(1) and has the potential to emit any regulated pollutant before control less than two hundred and fifty (250) tons per year. Therefore, the requirements of 326 IAC 2-2 are not applicable.

326 IAC 2-4.1 (New Sources of Hazardous Air Pollutants)

The boiler was constructed prior to July 27, 1997 and the HAP emissions from the entire source are less than the major source thresholds. Therefore, the requirements of 326 IAC 2-4.1 are not applicable.

326 IAC 2-6 (Emission Reporting)

This source is located in Marion County and the potential to emit of NO_x is greater than ten (10) tons per year. Therefore, 326 IAC 2-6 does apply.

326 IAC 5-1 (Opacity Limitations)

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of thirty percent (30%) any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings) as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

State Rule Applicability - One (1) boiler, one (1) heater

326 IAC 6-1-2 (Particulate Emission Limitations)

The non-attainment area limitations apply because this source is located in a county listed under 326 IAC 6-1-1(a), and, although the source does not have potential emissions greater than one hundred (100) tons per year, its actual emissions could be greater than ten (10) tons per year if emissions were calculated based on AP42 factors. However, the source stack tested the wood waste combustion boiler and established an emission factor of thirty-three hundredths pound of particulate matter per million Btu (0.33 lb PM/MMBtu). Pursuant to IAC 326 6-1-2(b) solid fuel-fired steam generators that have less than six million three hundred thousand (6,300,000) kcal per hour heat input (twenty-five million (25,000,000) Btu shall not emit gases with a particulate matter content of no greater than one and eight-hundredths (1.08) grams per million calories (six-tenths (0.6) pound per million Btu. The source was stack tested and emits PM at a rate of 0.33 pounds per million Btu, therefore, the source complies.

326 IAC 6-2-4 (Particulate Matter Emission Limitations for Sources of Indirect Heating)

326 IAC 6-2-4 does apply to the 14.11 MM Btu per hour Boiler, 001. 326 IAC 6-2-1 states that if any limitation established by this rule is inconsistent with applicable limitations contained in 326 IAC 6-1, then the limitations contained in 326 IAC 6-1 prevails. Therefore, compliance with 326 IAC 6-2-4 is satisfied by complying with the limitation specified under 326 IAC 6-1-2.

326 IAC 6-3-2 (Manufacturing Processes)

326 IAC 6-3-2 does not apply to combustion devices, therefore, this rule does not apply to the boiler, 001.

Conclusion

The operation of this boiler, 001, shall be subject to the conditions of the attached proposed MSOP 097-17957-00031.

Appendix A: Emissions Calculations
External Combustion Boiler
Wood Waste Combustion (uncontrolled)
Dry Wood

Page 1 of 2 TSD App A

Company Name: Indiana Veneers Corporation
Address City IN Zip: 1121 East 24th Street, Indianapolis, IN
CP: MSOP 097-17957-00031
Plt ID: 097-00031
Reviewer: Holly M. Stockrahm
Date: 21-Jul-03

| | |
|---------------------------------------|---------|
| Capacity (MMBtu/hr) | 14.11 |
| Capacity (tons/hr) | 0.82 |
| Higher Heating Value of Fuel (Btu/lb) | 8610 |
| Converted Capacity in MMBtu/hr | 14.1204 |

| | Pollutant | | | | | | |
|--------------------------------|-----------|-----------|------------|----------|-----------|-----------|-----------|
| | PM* | PM10* | PM2.5* | SO2 | NOx | VOC | CO** |
| Emission Factor in lb/MMBtu | 0.33 | 0.33 | 0.327 | 0.025 | 0.49 | 0.013 | 0.0913 |
| Potential Emissions in tons/yr | 20.394594 | 20.394594 | 20.2091886 | 1.545045 | 30.282882 | 0.8034234 | 5.6425043 |

Methodology

To convert from tons/hr capacity to MMBtu/hr capacity:

Heat Input Capacity (MMBtu/hr) = Capacity (tons/hr) x Higher Heating Value of wood fuel (Btu/lb) x (1 MMBtu/106 Btu/) x 2000 lbs/1 ton

PM and CO emission factors based on actual stack test data from July 1990, SO2, NOx, and VOC are based on AP 42 Emission Factors.

Emission Factors are from AP-42 Chapter 1.6 (revised 3/02), SCCs #1-0X-009-YY where X = 1 for utilities, 2 for industrial, and 3 for commercial/institutional; Y = 01 for bark-fired boilers, 02 for bark and wet wood-fired boilers, 03 for wet wood-fired boilers, and 08 for dry wood-fired boilers

Emissions (tons/yr) = Capacity (MMBtu/hr) x Emission Factor (lb/MMBtu) x 8760hrs/yr x 1ton/2000lbs

woodwaste.xls (created 9/01, revised 3/02 RLM)

**Appendix A: HAPs Emissions Calculations
External Combustion Boiler
Wood Waste Combustion (uncontrolled)
All Wood Waste Fuel Types**

Page 2 of 2 TSD App A

Company Name: Indiana Veneers Corporation
Address City IN Zip: 1121 East 24th Street, Indianapolis, IN
CP: MSOP 097-17957-00031
Plt ID: 097-00031
Reviewer: Holly M. Stockrahm
Date: 21-Jul-03

| | |
|---------------------------------------|---------|
| Capacity (MMBtu/hr) | 14.11 |
| Capacity (tons/hr) | 0.82 |
| Higher Heating Value of Fuel (Btu/lb) | 8610 |
| Converted Capacity in MMBtu/hr | 14.1204 |

| | Selected Hazardous Air Pollutants | | | | |
|--------------------------------|-----------------------------------|---------|--------------|-------------------|---------|
| | Acrolein | Benzene | Formaldehyde | Hydrogen Chloride | Styrene |
| Emission Factor in lb/MMBtu | 4.0E-03 | 4.2E-03 | 4.4E-03 | 1.9E-02 | 1.9E-03 |
| Potential Emissions in tons/yr | 2.5E-01 | 2.6E-01 | 2.7E-01 | 1.2E+00 | 1.2E-01 |

Methodology

To convert from tons/hr capacity to MMBtu/hr capacity:

Heat Input Capacity (MMBtu/hr) = Capacity (tons/hr) x Higher Heating Value of wood fuel (Btu/lb) x (1 MMBtu/106 Btu/) x 2000 lbs/1 ton

Emission Factors are from AP-42 Chapter 1.6 (revised 3/02), SCCs #1-0X-009-YY where X = 1 for utilities, 2 for industrial, and 3 for commercial/institutional; Y = 01 for bark-fired boilers, 02 for bark and wet wood-fired boilers, 03 for wet wood-fired boilers, and 08 for dry wood-fired boilers

Emissions (tons/yr) = Capacity (MMBtu/hr) x Emission Factor (lb/MMBtu) x 8760hrs/yr x 1ton/2000lbs

These factors include the five HAPs with the highest AP-42 emission factors.

woodwaste.xls (created 9/01 RLM)